



Data Sheet

FD30S Solid Flat Entrance Doorset









Richmond

Warwick

Walliams Flush

Walliams T&G

Certification and Accreditations		
Fire tested to:	BS 476: Part 20/22:1987	
	EN 1634-1: 2014 + A1:2018	
	All doorsets are bi-directionally tested	
Smoke	EN 1634-3: 2004	
Control test:		
3 rd Party	IFCC Certification Scheme	
Certification:		
UKCA	External – Yes	
Marking:	Internal – Not required	
PAS 24 /	PAS 24 2016 specification and Secured by	
Secured By	Design accredited	
Design:	-	

Sizes available (exc cill and add-ons) Min 833 x 1895

Max 1012 x 2115

Walliams min sizes are 685 x 1895

Hardwood add-ons available in sizes 15mm, 25mm and 50mm

External Colour options



White



Red





Green



Door Leaf Manufacturer: Door Leaf Type: Solid timber core Outer Frame Type: Frame Reinforcement: Intumescent Seals: Applied to the top and bottom of the door leaf the internal rebate and outside of the outer frame, and selected components Threshold: Slimline with fire retardant seal – Low Mobilic compliant OR 3mm air gap	of to
Outer Frame Type: Frame Reinforcement: Intumescent Seals: Applied to the top and bottom of the door leat the internal rebate and outside of the outer frame, and selected components Threshold: Slimline with fire retardant seal – Low Mobility compliant OR 3mm air gap	of to
Type: Frame Reinforcement: Intumescent Seals: Applied to the top and bottom of the door lead the internal rebate and outside of the outer frame, and selected components Threshold: Slimline with fire retardant seal – Low Mobility compliant OR 3mm air gap	of to
Reinforcement: Intumescent Seals: Applied to the top and bottom of the door lead the internal rebate and outside of the outer frame, and selected components Threshold: Slimline with fire retardant seal – Low Mobilic compliant OR 3mm air gap	of to
Seals: the internal rebate and outside of the outer frame, and selected components Threshold: Slimline with fire retardant seal – Low Mobili compliant OR 3mm air gap	of to
compliant OR 3mm air gap	
	,
Timber Cill None, 80x12, 100x30, 100x45, 144x30 144x options:	:45
Hinges: 4no Nico Lift off hinges	
Lock: ERA Surefire 4 point autofire locking system adjustable keeps	with
Cylinder: 3* Key-thumb turn cylinder, with 3 keys	
Handle: Lever-lever	
Viewer: 180 degrees fire rated viewer (optional)	
Knocker: Urn knocker (optional)	
Letter plate: Fire rated TS008 Letter plate with integral co (optional)	owl
Closer: Rutland TS5204 overhead closer OR Rutland TS11204 slide arm cam action closer	d
Security Chain: Hook type (optional)	
Numerals: 75mm aluminium (optional)	
Hardware finish: Anodised Gold or Silver Polished Gold or Chrome	
Toplight: Available with Pyrobelite or Pyronova glass height 260mm, Max height 400mm)	















